

Technical

- 1 For larger volumes, contact us
- 2 Dimensions H x W x D (in mm)
For specific internal and external dimensions, consult your dealer
- 3 Dust filters available separately
- 4 C18SR and C50SR models are equipped with a heating belt to combat frost.



**Wine
C18, C18S, C18SR⁴**



**Wine
C50S, C50SR⁴**



**Wine
C18In**

Conditioning capacity according to insulation ¹	up to 18m ³	up to 50m ³	up to 18m ³
Overall dimensions ²	440h x 548w x 380d	510h x 552w x 530d	465h x 676w x 390d
Weight	35 kg	45 kg	40 kg
Outer dimensions of wooden frame used for building-in ²	150 x 514 x 374	150 x 544 x 374	—
Cooling power	550 W	1200 W	550 W
Electrical power	230-240V-50 Hz	230-240V-50 Hz	230-240V-50 Hz
Coolant	R 404 a (no CFCs)	R 404 a (no CFCs)	R 404 a (no CFCs)
Diameter of condensate evacuation pipe	9 mm	9 mm	9 mm
Wooden frame supplied with the device	yes	yes	—
Connecting Kit	—	—	In option
Heating function	only C18S	yes	yes
Thermostat and thermometer with digital display	yes	yes	yes
Dust filter ³	yes	yes	yes
Reaction turbines	yes (condenser side)	yes	yes (condenser side)
Lighting (device with a pilot light)	no	yes	no
Guarantee	2 years	2 years	2 years
Installation guide supplied with the device	yes	yes	yes
Sound level to 1m - to 3m	49dB - 44dB	51dB - 47dB	47dB - 42dB

Optional Airtight Door




Made of lacquered steel, with polyurethane insulation, it guarantees optimal insulation.

Overall external dimensions

Height 1900mm
Width 600mm

Doorway dimensions

Height 1860mm
Width 590mm





Wine C50In



Wine SP100



Wine PC10

up to 50m ³	up to 100m ³	up to 10m ³
390h x 485w x 925d	1005h x 480w x 395d	2020h x 760w x 254d
45 kg	60kg	65kg
—	—	—
1200 W	2500 W	400 W
230-240V-50 Hz	230-240V-50 Hz	230-240V-50 Hz
R 404 a (no CFCs)	R 407 c (no CFCs)	R 404 a (no CFCs)
10 mm	10mm	—
—	—	—
In option	In option	—
yes	yes	—
yes	yes	yes
yes	yes	yes
yes	yes	yes
yes	no	no
2 years	2 years	2 years
yes	yes	yes
51dB - 47dB	57dB	44dB (distance 1m)



Built-in convenience

Insulated door with lock and frame, and with integrated wine conditioning unit.

Guarantees

All refrigeration units come with a 2 year warranty.

Installation principles

