

Technical Information



Wine C25,
C25S, C25SR



Wine C50S,
C50SR



Wine IN 25



Wine IN 50+



Wine SP40DU



Wine SP40CE



Wine SP100
& SP100-8



Wine Split TL6

Wine Split
TL10

Wine Split
TL16



Wine Arm



WM Door PC15



EC10 VIN

Conditioning capacity according to insulation*	up to 25m³	up to 50m³	up to 25m³	up to 50m³	up to 40m³	up to 15m³	up to 100m³	up to 8m³	up to 12m³	up to 17m³	up to 15m³	up to 15m³	up to 10m³
Overall dimensions**	381h x 540w x 524d	530h x 552w x 590d	540h x 540w x 630d	1044h x 500w x 478d	408h x 633w x 415d (int) 317h x 638w x 546d (ext)	262h x 517w x 327d (int) 408h x 633w x 415d (ext)	1005h x 480w x 395d	420h x 420w x 220d (Compressor Unit) 375h x 440w x 190d (Energizer Split) 160h x 480w x 430d (Ceiling evaporator) 360h x 430w x 210d (Wall Evaporator)			317h x 885w x 424d	2020h x 760w x 254d	787h x 475w x 230d
Weight	31 kg	45 kg	40 kg	51 kg	35kg (int) 26kg (ext)	17kg (int) 35kg (ext)	45kg (int) 15kg (ext)	23 kg	24 kg	26 kg	31kg	100kg (the unit)	26 kg
Outer dimensions of wooden frame used for building-in**	374h x 514w x 150d	150 x 544 x 374	-	-	-	-	-	-	-	-	-	-	-
Cooling power	550W	1200W	550W	1200W	900W at 15°C****	900W at 15°C****	2500W	8000 li- tres/390W	12000 litres/450W	17000 litres/780W	500W at 15°C	400W	465W
Power consumption	440W	900W	440W	900W	600W	600W	1250W	-	-	-		390W	185W
Electrical power	230-240V - 50 Hz	230-240V - 50 Hz	230-240V - 50 Hz	230-240V - 50 Hz	230-240V - 50 Hz	230-240V - 50 Hz	230-240V - 50 Hz	220-240V AC 50Hz			220-240V - 50Hz	230-240V - 50 Hz	220-240V - 50Hz
Coolant	R449A (no CFCs)	R407A (no CFCs)	R449A (no CFCs)	R407A (no CFCs)	R449A (no CFCs)	R449A (no CFCs)	R 407 c (no CFCs)	R134A CFC free 0.29kg			R449A (no CFCs)	R449A (no CFCs)	R134A (no CFCs)
Diameter of condensate evacuation pipe	9 mm	9 mm	9 mm	10 mm	internal 16mm external 20mm	internal 16mm external 20mm	10mm	10mm	10mm	10mm	-	-	-
Wooden frame supplied with the device	yes	yes	-	-	-	-	-	no	no	no	-	-	-
Connecting kit	-	-	IN option	IN option	-	-	-	Yes optional extra	Yes optional extra	Yes optional extra	-	-	-
Heating function	C25S and C25S/SR	yes	yes	yes	yes	yes	yes	Yes optional extra	Yes	Yes	-	-	-
Heating power	250W for CS25	500W	250W	500W	500W	500W	1000W	-	-	-	-	-	-
Thermostat and thermometer with digital display	yes	yes	yes	yes	yes	yes	yes	no	no	no	yes	yes	no
Dust filter***	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
Reaction turbines	yes (condenser side)	yes	yes (condenser side)	yes	yes	yes	yes (condenser side)	no	no	no	-	yes	no
Lighting (device with a pilot light)	no	yes	no	yes	no	no	no	-	-	-	no	no	no
Guarantee	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years
Installation guide supplied with the device	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
Sound level to 1m - 3m	49dB - 40dB	51dB - 47dB	43dB - 38dB	53dB - 50dB	49dB to 1m with optional sound proofing case or 59 (1m) and 49 (5m)	49dB to 1m with optional sound proofing case or 59 (1m) and 49 (5m)	53dB - 50dB	inside unit: 30db outside unit: 40 dB	inside unit: 30db outside unit: 40 dB	inside unit: 30db outside unit: 40 dB	38dB	42dB - 40dB	38dB
Heating strip to combat frost	only C25SR	yes	-	-	yes	yes	-	Yes optional extra	Yes optional extra	Yes optional extra	-	-	-

* For rooms or cellars of greater volumes than those stated, please contact us.
** Dimensions HxWxD (in mm). For sepecific internal and external dimensions, please contact us.
*** Genuine dust filters are recommended and available to purchase from Wine Corner Ltd
**** The cooling performance is dependent on the outside temperature. If the external temperature (air supply) is 35°C or above for any length of time, (2 weeks or more), the set temperature of 12°C for the cellar will not be maintained. Please talk to us if this might apply to your situation.

Guarantees
All refrigeration units are supplied with a 2 year guarantee

Installation
For more detailed information regarding installation, please referto Customer Services on our website, or contact us directly.

Coolants used in the units will always meet current legislation at the time of purchase.